
Product Specification Data



20-0W-A
Food Grade

Cover

Top Color	White
Thickness	
Material	PVC
Pattern	N/A
Durometer	

Carcass

Plies	2
Fabric	Polyester/Cotton
Anti-static	No
Laterally Rigid	Yes
Pulley Side Material	Polyester

Weight

0.04 lbs./in.-ft. (2.4 kg/m²)

Maximum Width

84" (2.1m)

Overall Thickness

0.091" (2.3mm)

Minimum Pulley at 70°F

Min Pulley <180°	1.5" (38.1mm)
Min Pulley Reverse Bend	1.5" (38.1mm)

Contact Temperature Range

5°F to 210°F (-15°C to 99°C)

Intermittent	Contact Mol Belting

Working Tension

Minimum	23-34 lbs./in. (4-6 N/mm)
Maximum	90 lbs./in. (15.8 N/mm)

Elongation

0.4% @ 23 lbs./in. (4 N/mm)
0.7% @ 34 lbs./in. (6 N/mm)
2% @ 90 lbs./in. (15.8 N/mm)

Coefficient of Friction

Mild Steel	0.22
S/S	0.24
UHMW	0.17

Splicing/Lacing Methods

Splicing	Finger Step Finger Splice
Lacing #1	Unibar #36 SP
Lacing #2	Alligator #1

Characteristics

FDA	Yes
Non-Marking	Yes
Flame Retardant	No
Release Characteristics	Good
Incline Conveying	No
Trough Conveying	No
Swan Neck Conveying	Fair
Metal Detectors (Dependent on Sensitivity)	Contact Mol Belting
Chemical Resistance	See Chart

Accessories

Edgecap	No
Guide	Yes
Cleats	No
Sidewall	No
Profile	No

mol belting systems

P 800.729.2358
E sales@molbelting.com
W molbelting.com
Rev. 11/11/2021